

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/25/2003

Reviewed on 07/10/2003

1 Identification of substance**Product details****Trade name: 275 CORE LF***Application of the substance / the preparation: Flux cored solder***Manufacturer/Supplier:**Kester
515 E. Touhy Ave.
Des Plaines, IL 60018Tel.(847) 297-1600
Fax.(847) 390-9338**Information department:**

MSDS Coordinator

Tel. (847) 699-5755

Emergency information:

CHEMTREC 24-Hour Emergency Telephone Number:

(800)424-9300

CHEMTREC 24-Hour Emergency Telephone Number (Outside of the U.S. and Canada):

(703)527-3887

2 Composition/Data on components**Chemical characterization***Description: Mixture of the substances listed below with nonhazardous additions.***Dangerous components:**

7440-31-5	tin	0-100%
7440-36-0	antimony	0-100%
7440-50-8	copper	0-100%
7440-22-4	silver	0-100%
7440-69-9	bismuth	0-100%
7440-66-6	Zinc	0-100%
144413-22-9	Denatured Acid Hydrogenation Gum Resin	≤ 2.5%
65997-06-0	Modified Rosin	≤ 2.5%
4196-86-5	pentaerythritol tetrabenzoate	≤ 2.5%

Additional information:*Composition and weight percent of solder alloys varies widely and can be determined by product label.
Flux in core is typically 1-3% by weight.***3 Hazards identification****WHMIS Hazard Symbols****Information pertaining to particular dangers for man and environment:***The product has to be labelled due to the calculation procedure of international guidelines.
May cause sensitisation by inhalation and skin contact.*

(Contd. on page 2)

USA

Material Safety Data Sheet


acc. to ISO/DIS 11014

Printing date 07/25/2003

Reviewed on 07/10/2003

Trade name: 275 CORE LF

(Contd. of page 1)

Classification system:**NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 1

Reactivity = 0

HMIS-ratings (scale 0 - 4)

HEALTH	1
FIRE	1
REACTIVITY	0

Health = 1

Fire = 1

Reactivity = 0

4 First aid measures**After inhalation:** Supply fresh air; consult doctor in case of complaints.**After skin contact:** Immediately wash with water and soap and rinse thoroughly.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Induce vomiting, if person is conscious. Seek medical help.**5 Fire fighting measures****Suitable extinguishing agents:**CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**Special hazards caused by the material, its products of combustion or resulting gases:**

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Aliphatic aldehydes

Protective equipment: Wear self-contained respiratory protective device.**Additional information** Flux in cored solder may ignite when the solder melts in a fire.**6 Accidental release measures****Person-related safety precautions:** Ensure adequate ventilation**Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.**Measures for cleaning/collecting:**

Melted solder will solidify on cooling and can be scraped up. Use caution to avoid breathing fumes if a gas torch is used to cut up large pieces.

7 Handling and storage**Handling:****Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.**Information about protection against explosions and fires:** Keep respiratory protective device available.**Storage:****Requirements to be met by storerooms and receptacles:** No special requirements.

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/25/2003

Reviewed on 07/10/2003

Trade name: 275 CORE LF

(Contd. of page 2)

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Store in dry conditions.

Exposure to sulfur or to high humidity will tarnish solder surface.

8 Exposure controls and personal protection

Additional information about design of technical systems: No further data; see item 7.

Components with limit values that require monitoring at the workplace:

7440-31-5 tin

PEL 2 mg/m³

Metal

REL 2 mg/m³

Tin, Metal

TLV 2 mg/m³

7440-36-0 antimony

PEL 0.5 mg/m³

REL 0.5 mg/m³

as Sb

TLV 0.5 mg/m³

7440-50-8 copper

PEL 0.1*;1** mg/m³

*fume **dusts & mists

REL 0.1*;1** mg/m³

*Copper fume, as Cu **Copper dusts & mists, as Cu

TLV 0.2*, 1** mg/m³

*fume; ** dusts&mists, as Cu

7440-22-4 silver

PEL 0.01 mg/m³

REL 0.01 mg/m³

TLV 0.1 mg/m³

65997-06-0 Modified Rosin

TLV Short-term value: 3 mg/m³, NE ppm

Long-term value: NE mg/m³, NE ppm

Additional information:

PEL = Permissible Exposure Limit (OSHA)

REL = Recommended Exposure Limit (NIOSH)

TLV = Threshold Limit Value (ACGIH)

OSHA = Occupational Safety and Health Administration

ACGIH = American Conference of Governmental Industrial Hygienists

NIOSH = National Institute for Occupational Safety and Health

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/25/2003

Reviewed on 07/10/2003

Trade name: 275 CORE LF

(Contd. of page 3)

Breathing equipment:

When ventilation is not sufficient to remove fumes from the breathing zone, a safety approved respirator or self-contained breathing apparatus should be worn.

Protection of hands:

Protective gloves

Material of gloves:

Cloth gloves

Nitrile rubber, NBR

Natural rubber, NR

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:

Tightly sealed goggles

Safety glasses

9 Physical and chemical properties**General Information**

Form: Solid
Color: Silver grey
Odor: Odorless

Change in condition

Melting point/Melting range: > 100°C (> 212°F)

Boiling point/Boiling range: Undetermined.

Flash point: > 93°C (> 199°F)

Danger of explosion: Product does not present an explosion hazard.

Density at 20°C (68°F): > 7 g/cm³

Solubility in / Miscibility with

Water: Insoluble.

10 Stability and reactivity

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Materials to be avoided: Strong acids, strong oxidizers.

Dangerous reactions No dangerous reactions known.

(Contd. on page 5)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/25/2003

Reviewed on 07/10/2003

Trade name: 275 CORE LF

(Contd. of page 4)

Dangerous products of decomposition:

When heated to soldering temperatures, the solvents are evaporated and rosin may be thermally degraded to liberate aliphatic aldehydes and acids.

11 Toxicological information**Acute toxicity:****LD/LC50 values that are relevant for classification:****65997-06-0 Modified Rosin**

Oral	LD50	> 4.000 mg/kg (Rat)
------	------	---------------------

Primary irritant effect:

on the skin: Possible local irritation by contact with flux or fumes.

on the eye: Smoke during soldering can cause eye irritation.

through inhalation:

Flux fumes during soldering may cause irritation and damage of mucous membranes and respiratory system.

through ingestion: May be harmful if swallowed.

Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

12 Ecological information

General notes: *Do not allow product to reach ground water, water course or sewage system.*

13 Disposal considerations**Product:****Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: *Disposal must be made according to official regulations.*

14 Transport information**DOT regulations:**

Hazard class: -

Not regulated.

Land transport ADR/RID (cross-border):

ADR/RID class: -

Not regulated.

(Contd. on page 6)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/25/2003

Reviewed on 07/10/2003

Trade name: 275 CORE LF

(Contd. of page 5)

Maritime transport IMDG:**IMDG Class:** -
Not regulated.**Air transport ICAO-TI and IATA-DGR:****ICAO/IATA Class:** -
Not regulated.**15 Regulations***USA The following information relates to product regulation specific to the USA.***SARA (Superfund Amendments and Reauthorization Act)***Section 355 (extremely hazardous substances):**None of the ingredient is listed.**Section 313 (Specific toxic chemical listings):*7440-36-0 | *antimony*7440-50-8 | *copper*7440-22-4 | *silver*7440-66-6 | *Zinc***TSCA (Toxic Substances Control Act):***All ingredients are listed.***California Proposition 65***Chemicals known to cause cancer:***WARNING:** *This product may contain a chemical in trace amounts known to the State of California to cause cancer.*7439-92-1 | *lead*7440-43-9 | *cadmium*7440-02-0 | *nickel**Chemicals known to cause reproductive toxicity:***WARNING:** *This product may contain a chemical in trace amounts known to the State of California to cause birth defects or other reproductive harm.*7439-92-1 | *lead*7440-43-9 | *cadmium***Carcinogenicity categories***EPA (Environmental Protection Agency)*7440-50-8 | *copper* | *D*7440-22-4 | *silver* | *D**IARC (International Agency for Research on Cancer)**None of the ingredients is listed.**NTP (National Toxicology Program)**None of the ingredients is listed.*

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 07/25/2003

Reviewed on 07/10/2003

Trade name: 275 CORE LF

(Contd. of page 6)

TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

*CANADA: The following information relates to product regulation specific to Canada.***Workplace Hazardous Materials Identification (WHMIS):***This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulation (CPR) and the MSDS contains all of the information required by the CPR.*

WHMIS Classification:

D2A

D2B

Components on Ingredient List for WHMIS:

Modified Rosin

tin

antimony

copper

silver

EUROPEAN UNION*The following information relates to product regulation specific to the directives of the European Union.***Risk phrases:***May cause sensitisation by inhalation and skin contact.***Safety phrases:***Keep out of the reach of children.**Do not breathe dust.**Avoid contact with skin.**Wear suitable gloves.**In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).**Dispose of this material and its container to hazardous or special waste collection point.**In case of accident by inhalation: remove casualty to fresh air and keep at rest.***16 Other information**

The information contained herein is based on data considered accurate and is offered solely for information, consideration and investigation. Kester extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The data on this Material Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and the necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Material Safety Data Sheet as a source for hazard information.

Department issuing MSDS: Product Safety**Contact:** Heather Holich, MSDS Coordinator

Tel. (847)699-5755